

AGM-65D IR Seeker <input checked="" type="checkbox"/>				F-16C VIPER	
01	Master Arm	Armed	↑	CL	
	Right HDPT	On	↑	LF	
	Allow Est. 3 minutes for Targeting POD to power				
02	ICP	A-G	↓	CM	
03	MFD R - SMS Page	Menu / SMS	↓	CR	
04	MFD R - Weapon Select	AG65D	↓	CR	
05	MFD R – VIS/BORE/PRE	Set to VIS	↓	CR	
06	MFD R – PWR ON/OFF AMG65	PWR ON	↓	CR	
07	MFD R – WPN	Empty OSB Twice / WPN	↓	CR	
	Allow Est. 5 minutes for AMG65 to power				
08	HUD – SOI	DMS Up	↓	CL	
	Confirm HUD SOI	Asterisk – Top Left			
09	HUD - RDR Cursor Slew / Zoom	Slew Seeker <input type="checkbox"/> to Target Area	↓	CL	
10	HUD – Ground Stabilize	TMS Up	↓		
	Confirm MFD R – SOI	else DMS Down			
11	MFD R – RDR Cursor Slew / Zoom	Identify Target	↓	CL	
12	MFD R - Target Lock (within 7nm)	TMS Up	↓	CL	
	Note: TMS Down will reset lock, but also set HUD as SOI				
	MFD R	Cross hairs solid / vibrating			
13	Stick	Weapon Release	↓		
14	Comm	“Rifle”			
	Repeat Steps 11 – 14 for subsequent targets				
END OF PROCEDURE					